



(43) International Publication Date  
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number  
**WO 2005/020656 A3**

(51) International Patent Classification<sup>7</sup>: **H05K 13/04**

(21) International Application Number:  
PCT/JP2004/012453

(22) International Filing Date: 24 August 2004 (24.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003-301838 26 August 2003 (26.08.2003) JP  
2003-378373 7 November 2003 (07.11.2003) JP

(71) Applicant (for all designated States except US): MAT-  
SUSHITA ELECTRIC INDUSTRIAL CO., LTD.  
[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka  
5718501 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MAENISHI,**

Yasuhiro. **KONISHI, Chikashi. YOSHIDA, Ikuo.**  
**NISHIDA, Hiroyoshi. MATSUMOTO, Masaya. YA-**  
**MASAKI, Akihito. YAMAZAKI, Takuya.**


(74) Agent: **NII, Hiromori;** c/o NII Patent Firm, 3rd Floor,  
Shin-Osaka Suehiro Center Bldg., 11-26, Nishinakajima  
3-chome, Yodogawa-ku, Osaka-shi, Osaka 5320011 (JP).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,  
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,  
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,  
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: COMPONENT VERIFICATION METHOD



(57) Abstract: A component verification method for a mounter (100) that is capable of performing component verification with less labor, is comprised of: a position specification step (S12A) of specifying a placement position in the mounter (100) where a component tape is placed; a read step (S13) of reading component information from an IC tag (426b) that is attached to the component tape or a reel (426); and a verification step (S14) of verifying the component information and the placement position against component arrangement data that indicates components that should be mounted onto the board as well as a position where the component tape should be placed.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:  
7 July 2005

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*